

Catalog Number: SS03/20M
Product ID: 7TCA296120R0001
EAN Number: 05020963020933
Status: Active

Inherent Low Fire Hazard Conduit, Nominal Conduit Size 3mm, Reel Length 20 Meters, 316 Stainless Steel, Corrosion Resistant

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Brand Name	Adaptaflex
Type	Low Fire Hazard Conduit
Special Features	Very High UV Protection and Fatigue Life
Application	Indoors / Outdoors - Corrosive Environments
Trade Size	3mm
Length	20 m
Flexibility	Very High
Material	Stainless Steel

European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal diameter	3mm
Material	Stainless steel
Surface protection	Untreated
Sheathing material 1st coating	Not sheathed
Operating temperature	-50-+350°C
Degree of protection (IP)	IP40
Colour	Metallic
Bending strength	Flexible

Packaging

Outer Quantity	1
Outer Dimensions (inches)	1x1x1
Weight Uom	0.15 lbs. Each

Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com