


**TABLE No. 1 STEEL DOUBLE TYPE "B" MINIMUM BORE SPROCKETS**


Type DB

PART No.	DIAMETERS		No. TEETH	TYPE	BORE		DIMENSIONS					Wt. Lbs.
	OUTSIDE	PITCH			STOCK	MAX.*	T	M	L MAX.	P	H	
<b>SMALLER SIZES ON PRECEDING PAGE</b>												
D40B23	3.94"	3.672"	23	DB	5/8	2"	.275"	.841"	1 5/8"	25/32"	3"	3.3
D40B24	4.10	3.831	24	DB	5/8	2 1/4	.275	.841	1 5/8	25/32	3 1/4	3.6
D40B25	4.26	3.989	25	DB	5/8	2 1/4	.275	.841	1 5/8	25/32	3 1/4	3.9
D40B26	4.42	4.148	26	DB	5/8	2 1/4	.275	.841	1 5/8	25/32	3 1/4	4.1
D40B30	5.06	4.783	30	DB	7/8	2 1/4	.275	.841	1 5/8	25/32	3 1/4	5.1
D40B32	5.38	5.101	32	DB	7/8	2 1/4	.275	.841	1 5/8	25/32	3 1/4	5.8
D40B35	5.86	5.578	35	DB	7/8	2 1/4	.275	.841	1 5/8	25/32	3 1/4	6.8
D40B36	6.02	5.737	36	DB	15/16	2 1/2	.275	.841	1 5/8	25/32	3 3/4	7.9
D40B40	6.65	6.373	40	DB	15/16	2 1/2	.275	.841	1 3/4	29/32	3 3/4	10.1
D40B42	6.97	6.691	42	DB	15/16	2 1/2	.275	.841	1 3/4	29/32	3 3/4	10.8
D40B45	7.45	7.168	45	DB	15/16	2 1/2	.275	.841	1 3/4	29/32	3 3/4	12.1
D40B48	7.93	7.645	48	DB	15/16	2 1/2	.275	.841	1 3/4	29/32	3 3/4	13.3
D40B52	8.57	8.281	52	DB	15/16	2 1/2	.275	.841	1 3/4	29/32	3 3/4	15.2
D40B54	8.89	8.599	54	DB	15/16	2 1/2	.275	.841	1 3/4	29/32	3 3/4	16.2
D40B60	9.84	9.554	60	DB	15/16	2 1/2	.275	.841	1 3/4	29/32	3 3/4	19.3
D40B68	11.12	10.826	68	DB	1 3/16	2 3/4	.275	.841	2 1/8	1 9/32	4 1/4	25.7
D40B72	11.75	11.463	72	DB	1 3/16	2 3/4	.275	.841	2 1/8	1 9/32	4 1/4	28.3
D40B76	12.39	12.099	76	DB	1 3/16	2 3/4	.275	.841	2 1/8	1 9/32	4 1/4	31.0
D40B84	13.66	13.372	84	DB	1 3/16	2 3/4	.275	.841	2 1/8	1 9/32	4 1/4	37.6
D40B96	15.57	15.281	96	DB	1 3/16	2 3/4	.275	.841	2 1/8	1 9/32	4 1/4	47.7
D40B102	16.53	16.236	102	DB	1 3/16	2 3/4	.275	.841	2 1/8	1 9/32	4 1/4	53.3
D40B112	18.12	17.828	112	DB	1 3/16	2 3/4	.275	.841	2 1/8	1 9/32	4 1/4	63.3

Hardened Teeth

\* Maximum bore shown is with standard keyway and setscrew over keyway. Slightly larger bores are possible with no keyway, shallow keyway or setscrew at angle to keyway

† Hub is recessed for chain clearance.

These Type "B" sprockets are made without keyways or setscrews. They are furnished with a minimum bore which can be rebored to size and keywayed for a reasonable extra charge.