



X-Series Intrinsically Safe Flashlight

200
Lumens

- cETLus, ATEX, and IECEx listed Intrinsically Safe
- Beam distance rated at 143 meters
- Polymer housing
- Meets the requirements of NFPA-1971-8.6 (2013)



This Flashlight is cETLus, ATEX, and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present. The XPP-5418GX uses a CREE® LED rated at 200 lumens that works in conjunction with a high-efficiency deep parabolic reflector to create a usable flashlight beam rated at 143 meters. The tail switch provides momentary or constant-on functionality. Meets the requirements of NFPA-1971-8.6 (2013). Power comes from 3 AA premium batteries.

INTRINSICALLY SAFE



XPP 5418GX

X-Series Intrinsically Safe Flashlight

FEATURES

- cETLus, ATEX, and IECEx listed Intrinsically Safe for use in both above and below ground hazardous locations where explosive gases and dusts may be present
- CREE® LED technology – 50,000 + hours LED life
- Momentary or constant-on flashlight
- Sharp focused flashlight beam for distance illumination
- Glass filled nylon polymer housing
- Non-slip grip
- Tail switch
- Dustproof / Waterproof
- Impact and chemical resistant
- Meets Requirements of NFPA-1971-8.6 (2013)
- 3 AA batteries (not included)
- Limited Lifetime Warranty









Single tail switch



High-efficiency deep
parabolic reflector

SPECIFICATIONS

- Lumens: 200
- Run-time: 10.5 hrs
- Beam Distance: 143 meters
- Candela: 5129
- Water / Dust Rating: IP-67
- Drop Rating: 2 meters
- Dimensions: Length 5.6 in., Head Diameter 1.5 in., Handle Diameter .75 x 1.4 in., Weight 5.4 oz.

FL 1 STANDARD		
 200 LUMENS	 10.5h	 143m
 5129cd	 2m	 1m

SAFETY RATING

cETLus, ATEX, and IECEx listed Intrinsically Safe

Model	UPC 0 17398
XPP-5418GX	80619 0