



SPECIFICATION SHEET

148-6000

TOP GRAIN GOATSKIN LEATHER PROTECTOR FOR NOVAX® GLOVES – GAUNTLET CUFF

- Top grain goatskin leather construction is the softest, most abrasion-resistant leather and is highly recommended for applications requiring tactile sensitivity
- Top grain leather is smooth, provides durability and dexterity
- Split leather gauntlet cuff for added forearm protection and allows for fast removal
- Straight thumb increases comfort in closed-fisted work
- Nylon strap with buckle for a secure, personal fit
- Cotton color binding denotes sizing
- Meets ASTM F696-06 (2011) standard

APPLICATIONS

- For use with Class 1-4 rubber insulating Novax® gloves. Cover glove to be used only for mechanical protection for rubber insulating gloves. Not to be used for electrical protection per ASTM F696-06 - 2011.

TECHNICAL DATA

MATERIAL	100% Goatskin Leather				
COLOR	Natural				
CUFF STYLE	Gauntlet				
SIZES	8 - 12				
PACKAGING	12 per dozen, 24 pair per case				
CASE DIMENSIONS	15.2" x 15.2" x 8.1" / 38.5cm x 38.5cm x 20.5cm				
CASE WEIGHT	8	9	10	11	12
	14.3 lbs 6.5 kg	15.4 lbs 7.0 kg	16.5 lbs 7.5 kg	17.6 lbs 8.0 kg	18.7 lbs 8.5 kg
COO	China				

MAX USE VOLTAGE

CLASS	AC VOLTS	DC VOLTS
1 - 4	7,500 - 36,000	11,250 - 54,000

10 NOVAX™ by G.B. INDUSTRIES
ANSI / ASTM CLASS 1 MADE IN MALAYSIA TYPE 1
MAX USE VOLT 7500V AC

10 NOVAX™ by G.B. INDUSTRIES
ANSI / ASTM CLASS 4 MADE IN MALAYSIA TYPE 1
MAX USE VOLT 36000V AC

BARCODES

ITEM	BAG	DOZEN	CASE
148-6000/8	---	01616314067296	02616314067295
148-6000/9	---	01616314067289	02616314067288
148-6000/10	---	01616314067319	02616314067318
148-6000/11	---	01616314067326	02616314067325
148-6000/12	---	01616314067333	02616314067332



DIMENSIONS (in/cm)

	8	9	10	11	12
A	14 / 35.6	14 / 35.6	14 / 35.6	13.9 / 35.3	13.9 / 35.3
B	5 / 12.7	5.25 / 13.3	5.25 / 13.3	6 / 15.2	6.25 / 15.9
C	6.1 / 15.5	5.75 / 14.6	5.6 / 14.2	5.5 / 14	5.25 / 13
H	Red	Green	Brown	Blue	Black

Leather Thickness: 0.8mm / Cuff Thickness: 1.6mm

