

Standard twist, plain arbor hole




EDP 763988

Standard twist knot wheel brushes feature twisted knots for aggressive brushing action with a good surface finish. They are ideal when heavy-duty or severe cleaning is required.

Standard twist, threaded arbor hole



EDP 764008

| Diameter [Inches] | Arbor hole/thread size [Inches] | Included adapter [Inches] | Wire size and EDP number | | MSFS max. [RPM] |  |
|--------------------------|---------------------------------|---------------------------|--------------------------|--------|-----------------|---|
| | | | .014 | .020 | | |
| Carbon steel wire | | | | | | |
| 4 | 1/2 | 3/8 | 763919 | - | 20,000 | 5 |
| 4 | 5/8-11 | - | - | 763926 | 20,000 | 5 |
| 6 | 5/8 | 1/2 | 763988 | - | 9,000 | 5 |
| 6 | 5/8 | 1/2 | - | 763995 | 9,000 | 5 |
| 6 | 5/8-11 | - | - | 764008 | 9,000 | 5 |
| 8 | 5/8 | - | 764046 | - | 7,000 | 5 |
| 8 | 5/8 | - | - | 764053 | 7,000 | 5 |


Stringer bead twist knot wheel brushes are tightly twisted for low flex, high impact brushing action. Designed for root and hot pass weld cleaning in pipe joining applications.

Also for general use where a narrow face, aggressive brush is desired.

Stringer bead twist, threaded arbor hole



EDP 764015

| Diameter [Inches] | Thread size [Inches] | No. knots | Wire size and EDP number | | MSFS max. [RPM] |  |
|------------------------------------|----------------------|-----------|--------------------------|--|-----------------|---|
| | | | .020 | | | |
| Carbon steel wire | | | | | | |
| 4 | 5/8-11 | 32 | 763940 | | 20,000 | 5 |
| 6 | 5/8-11 | 48 | 764015 | | 12,500 | 5 |
| 7 | 5/8-11 | 56 | 764039 | | 9,000 | 5 |
| Stainless steel wire (INOX) | | | | | | |
| 4 | 5/8-11 | 32 | 763957 | | 20,000 | 5 |
| 6 | 5/8-11 | 48 | 764022 | | 12,500 | 5 |