

ONIX™

EXTREME LIGHTWEIGHT COMFORT

**PART**

SB4910S***

SB4910ST****

SB4920S***

SB4970S***

SB4980S***

SGR4910ST***

SGR4920S**

SGR4920ST***

LENS
 Clear

 Clear (Anti-Fog)

 Gray

 Silver Mirror

 Indoor/Outdoor Mirror

 Clear (Anti-Fog)

 Gray

 Gray (Anti-Fog)
PART

SN4920S**

SN4980S**

S04910S**

SP4910S**

SR4980S**

LENS
 Gray

 Indoor/Outdoor Mirror

 Clear

 Clear

 Indoor/Outdoor Mirror

- Cushioned temple tips provide non-slip comfort.
- Lightweight frame and suspended lens design provide perfect fit for a variety of users.
- Ratcheting temples provide different angles for perfect view and fit.
- Adjustable nose piece provides 3 different angles, allowing the user to find the most comfortable fit.
- Suspended lens provides stylish look, comfort fit, panoramic view and maximum protection, filters 99.9% of harmful UV rays.

GENERAL SPECIFICATION

Bridge: 15mm

Lens Base: 8 Curve

Lens Size Diagonal: 141mm

Lens Size Vertical: 45mm

Lens Thickness: 2.2mm

Overall Length (Lens-Tip): 161mm

Overall Width (Hinge-Hinge): 128mm

PD: 68mm

Weight: 27gm

PACKAGING














Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs

ONIX™**EXTREME LIGHTWEIGHT COMFORT**

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	8 Base Curve, wrap around design with full front, up & side protection
Frame	Polycarbonate	Polycarbonate
Side Shields	Polycarbonate	Integral to lens
Nose Piece	Bridge-Polycarbonate	Angle adjustable nose piece with co-material soft pad
	Nose Pad - TPE	
Temple	Side arm - Polycarbonate	Spatula, co-material co-injection - durable PC temple with soft cushion tip
	Tip - TPE	
Ratchets	Nylon	3 lens angle adjustment
Hinge	Polycarbonate	3 barrel type, integral to frame/ratchets
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB4910S	 Clear	P Z87 + U6	P Z87 +
SB4910ST	 Clear (Anti-Fog)	P Z87 + U6	P Z87 +
SB4920S	 Gray	P Z87 + U6 L2.5	P Z87 +
SB4970S	 Silver Mirror	P Z87 + S	P Z87 +
SB4980S	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 +
SGR4910ST	 Clear (Anti-Fog)	P Z87 + U6	P Z87 +
SGR4920S	 Gray	P Z87 + U6 L2.5	P Z87 +
SGR4920ST	 Gray (Anti-Fog)	P Z87 + U6 L2.5	P Z87 +
SN4920S	 Gray	P Z87 + U6 L2.5	P Z87 +
SN4980S	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 +
S04910S	 Clear	P Z87 + U6	P Z87 +
SP4910S	 Clear	P Z87 + U6	P Z87 +
SR4980S	 Indoor/Outdoor Mirror	P Z87 + U6 L1.7	P Z87 +

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact