



Ensemble™

60" x 32" tile shower wall set w/AIP backerboards
71124106



Features

- Complete three-piece wall set with backerboards.
- Durable high-gloss finish provides a smooth, shiny surface that is easy to clean.
- Tongue-and-groove interlocking joints form a seamless appearance and simplify installation.
- Realistic tile look.
- Features convenient shelving.
- Includes factory-installed Aging in Place backerboards for future grab bar installation.

Material

- Made from solid Vikrell® material for strength, durability, and lasting beauty.

Installation

- Modular design allows it to be moved around corners and through doorways with ease.



Recommended Products/Accessories

- 5425-59 Frameless sliding bath door
- 5427-59 Frameless sliding bath door
- 542808-59 Frameless sliding bath door
- 80001012 12" straight grab bar
- 80001018 18" straight grab bar
- 80001024 24" straight grab bar
- 80011032 32" straight grab bar
- 80001036 36" straight grab bar
- K-23733 Vikrell® cleaner

Codes/Standards

- CSA B45.5/IAPMO Z124
- ASTM E162
- ASTM E662

Warranty – Bathing Fixtures (and Kitchen and Utility Sinks Made of Solid Vikrell® Material)

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

| Color | Code | Description |
|---|------|----------------|
|  | 0 | White |
|  | 96 | KOHLER Biscuit |

1-800-STERLING (1-800-783-7546)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current Specification Sheet, go to www.sterlingplumbing.com.



Ensemble™
60" x 32" tile shower wall set w/AIP backerboards
71124106

No image available.

This product is a component and not intended to be a standalone installation.

Technical Information

All product dimensions are nominal.

Installation: Three-wall alcove

Notes

Install this product according to the installation instructions.

Product is designed to be used with a single-hole mixer valve with an escutcheon cover not to exceed 7-3/4" (197 mm) in width.

Bath cannot be installed without the wall surround.

Width of back wall at top transitions from 60" (1524 mm) at the front to 59-3/8" (1508 mm) in the back corners. Furring strips approximately 1/4" (6 mm) thick should be used at the back corner studs if drywall is to be installed over the nailing flange.