

Liquidtight

Straight Component Type Connectors

Features

- Assembled with Zinc Die Cast Locknut

Application


- For use with metallic and non-metallic "Type B" Liquidtight Conduit

Standard Material

- Zinc Die Cast



E148716



Topaz Cat. No.	UPC	Conduit Size	Unit Ctn.	Ship Case	Weight Case	A	B	C
470	14250	3/8" 1/2" KO	20	200	36	1.446	1.260	.400
471	14260	1/2"	20	200	40	1.500	1.385	.420
472	14270	3/4"	10	100	23	1.603	1.720	.420
473	14280	1"	5	50	20	1.792	1.900	.550
474	14290	1 1/4"	5	50	30	1.900	2.290	.546
475	14300	1 1/2"	2	20	15	1.737	2.633	.520
476	14310	2"	2	20	24	2.080	3.156	.585
477	14320	2 1/2"	-	1	1	3.025	4.205	.775
478	14330	3"	-	1	2	3.530	4.910	.920
479	14340	3 1/2"	-	1	3	3.660	5.470	.920
480	14350	4"	-	1	4	3.875	5.925	.987

WITH
INSULATED THROAT

470i	14360	3/8" 1/2" KO	20	200	40	1.446	1.260	.400
471i	14370	1/2"	20	200	34	1.500	1.385	.420
472i	14380	3/4"	10	100	25	1.603	1.720	.420
473i	14390	1"	5	50	22	1.792	1.900	.550
474i	14400	1 1/4"	5	50	34	1.900	2.290	.546
475i	14410	1 1/2"	2	20	18	1.737	2.633	.520
476i	14420	2"	2	20	28	2.080	3.156	.585