

Liquidtight

90° Component Type Connectors

Features

- Assembled with Zinc Die Cast Locknut

Application

- For use with metallic and non-metallic "Type B" Liquidtight Conduit

Standard Material

- Zinc Die Cast



E148716

Topaz Cat. No.	UPC	Conduit Size	Unit Ctn.	Ship Case	Weight Case	A	B	C
490	14610	3/8" 1/2" KO	10	100	27	2.062	2.340	.52
491	14620	1/2"	10	100	28	2.220	2.340	.52
492	14630	3/4"	10	100	38	2.550	3.550	.68
493	14640	1"	5	50	32	2.820	3.785	.67
494	14650	1 1/4"	2	20	20	3.362	3.960	.70
495	14660	1 1/2"	2	20	26	3.450	4.130	.70
496	14670	2"	1	10	19	4.036	4.700	.57
497	14680	2 1/2"	-	1	4	5.215	5.375	.77
498	14690	3"	-	1	5	6.100	6.500	1.10
499	14700	3 1/2"	-	1	6	6.715	7.450	1.10
500	14710	4"	-	1	7	6.780	8.00	1.10

WITH INSULATED THROAT

490i	14720	3/8" 1/2" KO	10	100	30	2.062	2.340	.52
491i	14730	1/2"	10	100	27	2.220	2.340	.52
492i	14740	3/4"	10	100	39	2.550	3.550	.68
493i	14750	1"	5	50	33	2.820	3.785	.67
494i	14760	1 1/4"	2	20	21	3.362	3.960	.70
495i	14770	1 1/2"	2	20	26	3.450	4.130	.70
496i	14780	2"	1	10	20	4.036	4.700	.57

