



3/8" DRIVE SHALLOW SOCKETS, 12 POINT, SAE

High-Polished Chrome Finish

	A	B	C	D	E	F		
Product Code	Size (Inches)	OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)
31208	1/4	1	1 1/16	7/16	1 1/32	9/16	7/32	17/32
31210	5/16	1	1 1/16	15/32	3/8	17/32	1/4	17/32
31212	3/8	1	1 1/16	9/16	3/8	1/2	9/32	17/32
31214	7/16	1	1 1/16	5/8	1 1/32	17/32	13/32	17/32
31216	1/2	1	3/4	3/4	13/32	19/32	7/16	-
31218	9/16	1 1/16	25/32	25/32	17/32	5/8	17/32	-
31220	5/8	1 1/16	7/8	7/8	19/32	1 1/16	19/32	-
31222	1 1/16	1 1/16	15/16	15/16	1/2	1 1/16	21/32	-
31224	3/4	1 1/8	1	1	9/16	23/32	23/32	-
31226	13/16	1 1/8	1 1/8	1 1/8	9/16	23/32	25/32	-
31228	7/8	1 7/32	1 3/16	1 3/16	2 1/32	13/16	27/32	-
31230	15/16	1 7/32	1 1/4	1 1/4	2 1/32	13/16	27/32	-
31232	1	1 7/32	1 5/16	1 5/16	1 1/16	13/16	31/32	-

Fed. Spec: ANSI B107.110

31923 9 Piece 3/8" Drive Shallow 12 Point Socket Set on Clip Rail

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
31208	1/4	31214	7/16	31220	5/8
31210	5/16	31216	1/2	31222	1 1/16
31212	3/8	31218	9/16	31224	3/4

31927 10 Piece 3/8" Drive Shallow 12 Point Socket Set on Clip Rail

Product Code	Size (mm)	Product Code	Size (mm)	Product Code	Size (mm)
31208	1/4	31210	5/16	31212	3/8
31214	7/16	31216	1/2	31218	9/16
31220	5/8	31222	1 1/16	31224	3/4
31226	13/16				

31925 13 Piece 3/8" Drive Shallow 12 Point Socket Set on Clip Rail

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
31208	1/4	31218	9/16	31228	7/8
31210	5/16	31220	5/8	31230	15/16
31212	3/8	31222	1 1/16	31232	1
31214	7/16	31224	3/4		
31216	1/2	31226	13/16		



3/8" DRIVE SHALLOW SOCKETS, 6 POINT, SAE

High-Polished Chrome Finish

	A	B	C	D	E	F		
Product Code	Size (Inches)	OAL (Inches)	Drive End Diameter (Inches)	Working End Diameter (Inches)	Broach Depth (Inches)	Bolt Clearance Depth (Inches)	Bolt Clearance Diameter (Inches)	Nose Length (Inches)
31108	1/4	1	1 1/16	7/16	1 1/32	9/16	7/32	17/32
31110	5/16	1	1 1/16	15/32	3/8	17/32	1/4	17/32
31112	3/8	1	1 1/16	9/16	3/8	1/2	9/32	17/32
31114	7/16	1	1 1/16	5/8	1 1/32	17/32	13/32	17/32
31116	1/2	1	3/4	3/4	13/32	19/32	7/16	-
31118	9/16	1 1/16	25/32	25/32	17/32	5/8	17/32	-
31120	5/8	1 1/16	7/8	7/8	19/32	1 1/16	19/32	-
31122	1 1/16	1 1/16	15/16	15/16	1/2	1 1/16	21/32	-
31124	3/4	1 1/8	1	1	9/16	23/32	23/32	-
31126	13/16	1 1/8	1 1/8	1 1/8	9/16	23/32	25/32	-
31128	7/8	1 7/32	1 9/16	1 3/16	21/32	13/16	27/32	-
31130	15/16	1 7/32	1 1/4	1 1/4	21/32	13/16	27/32	-
31132	1	1 7/32	1 5/16	1 5/16	1 1/16	13/16	31/32	-

Fed. Spec: ANSI B107.110

31922 9 Piece 3/8" Drive Shallow 6 Point Socket Set on Clip Rail

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
31108	1/4	31114	7/16	31120	5/8
31110	5/16	31116	1/2	31122	1 1/16
31112	3/8	31118	9/16	31124	3/4

31924 13 Piece 3/8" Drive Shallow 6 Point Socket Set on Clip Rail

Product Code	Size (Inches)	Product Code	Size (Inches)	Product Code	Size (Inches)
31108	1/4	31118	9/16	31128	7/8
31110	5/16	31120	5/8	31130	15/16
31112	3/8	31122	1 1/16	31132	1
31114	7/16	31124	3/4		
31116	1/2	31126	13/16		



31216

31208



31923



31927



31925

Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 12 point fasteners.



31116


31108



31922



31924



Features

- SUPERTORQUE® lobular openings for greater turning power without deforming the fastener.
- Designed for maximum engagement on 6 point fasteners.

